

you can
Canon

PIXMA iX5000



Advanced A3+ printer for high-speed, high-quality document, photo and graphics printing.

The PIXMA iX5000 is part of the Canon A3+ inkjet printer range.

The whole range consists of: PIXMA Pro9500, PIXMA Pro9000, **PIXMA iX5000**, PIXMA iX4000.

Embargo Date: 21 February 2006
Sales Start Date: April
Target Market: home office & small office

Key Features

- Superior print speed: up to 25ppm mono & 17ppm colour (A4)
- A3+ photo lab quality print in approx. 166 seconds in Standard mode*
- Photo lab quality using FINE Print head with Micro-Nozzles ejecting 2pl droplets giving a maximum 4800*x1200dpi print resolution
- Sharp and crisp text printing with rich and vibrant colour graphics
- ChromaLife100 system for long-lasting, beautiful photos*
- Transparent Single Ink system
- PictBridge-ready for direct photo printing from digital cameras
- 150-sheet Auto Sheet Feeder
- Windows & Mac OS X compatible; USB 2.0 Hi-Speed
- Robust design

* see specifications

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA iX5000	0532B016AA	4960999359915	£329 / €475

What's in the box:

PIXMA iX5000 A3+ Photo printer, Print head, Canon Genuine Ink Tanks (PGI-5BK, CLI-8Y, CLI-8M, CLI-8C), Set-up and software CDs, Power Cord, Printed manuals, warranty leaflet.

Consumables**	Mercury Code	EAN Code	Recommended Retail Price
Ink tank CLI-8C	0621B001AA	4960999272672	£9.99 / €13.99
Ink tank CLI-8M	0620B001AA	4960999272702	£9.99 / €13.99
Ink tank CLI-8Y	0623B001AA	4960999272825	£9.99 / €13.99
Ink tank PGI-5BK	0628B001AA	4960999273020	£11.99 / €15.99

** For full list of media types see technical specifications

you can
Canon

PIXMA iX5000



Technical Specifications

Resolution	Up to 4800x1200dpi ¹
Print engine	4-ink FINE print head with 2 pl Micro-Nozzles
Colour management	ICM, ColorSync, Exif Print
Mono print speed	Up to 25ppm (Max.), 12.2ppm (Std)
Colour print speed	Text & Graphics: Up to 17ppm (Max.), 9.5ppm (Std) A4 Full Page: Approx. 97 seconds (Std)
Photo print speed	Borderless 4" x 6": Approx. 51 seconds (Std) A3+: Approx. 166 seconds (Std) (28x36cm photo on A3+ Photo paper)
Media type	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-101), Photo Paper Plus Double Sided (A4 & 13 x 18cm), Glossy Photo Paper (GP-401 & GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), Super White Paper (SW-201), Transparency (CF-102), T shirt Transfer (TR-301)
Media weight	Sheet feeder: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²
Media input	Sheet feeder: 150 sheets
Media size	Sheet feeder: A3+, A3, LDR+, LDR, A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 25x30cm, 20x25cm, 5" x 7", 4" x 6"
Borderless printing	Available using Photo Paper Pro (A3+, A3, A4 & 4" x 6"), Photo Paper Plus Glossy (A3+, A3, A4, 5" x 7" & 4" x 6"), Photo Paper Plus Semi Gloss (A3+, A3, A4 & 4" x 6"), Photo Paper Plus Double Sided (A4 & 5" x 7"), Glossy Photo Paper (A3+, A3, A4, 4" x 6" & Credit Card), Matte Photo Paper (A3, A4)
Two sided printing	Available by manual operation only using Photo Paper Plus Double Sided, Super White Paper or plain paper in A3+, A3, A4, B5, A5, Letter & 5" x 7" sizes (Windows only)
Ink cartridge configuration	Single Ink technology - 4 separate ink tanks (PGI-5BK, CLI-8C, CLI-8M, CLI-8Y)
Black ink tank life	PGI-5BK: 380 pages at 5% coverage ² PGI-5BK: 1400 pages (Printing ISO/JIS-SCID N5) ³
Colour ink tank(s) life	400 pages at 5% coverage per ink tank ² Cyan: 710 pages, Magenta: 470 pages, Yellow: 460 pages, (Printing ISO/JIS-SCID N5) ³

PC interface & connectivity	USB 2.0 Hi-speed ⁵
Camera interface & connectivity	Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders
Operating system requirements	Windows: PC with Windows XP, Windows 2000, Windows Me or Windows 98, USB interface ⁴ , CD-ROM Drive. Free hard disk space: 300 MB for Windows XP/2000 and Windows Me/98. Mac: Macintosh computer with Mac OS X v10.2.8 or later, USB interface. Free hard disk space: 350 MB for Mac OS X v10.2.8 or later.
Driver features	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Photo Noise Reduction, Vivid Photo
Software included	Windows: Easy-WebPrint, Easy-PhotoPrint, PhotoRecord and Easy-PrintToolBox. Mac: Easy-PhotoPrint
Power source	AC 100 - 240V
Power consumption	Approx. 0.8W (standby), approx. 17W (printing)
Operating temperature range	5° - 35° C
Operating humidity	10 - 90% RH (no condensation)
Acoustic noise levels	Approx. 37dB (A) (best quality mode)
Dimensions (W x D x H)	601x317.6x193.2mm
Weight	Approx. 9.3 kg

¹ Ink droplets can be placed with a minimum pitch of 1/4000 inch.

² Print volume figures may vary with the content of the document and the print mode. Black calculation based on an average of four printers run continuously until ink out printing 1500 characters per page, normal text, in default mode on plain paper using Windows XP and Word 2003.

³ Print volume figures may vary with the content of the document and the print mode. Colour calculation based on an average of four printers run continuously until ink out printing the ISO/JIS-SCID N5 pattern in default mode on plain paper using Windows XP and Word 2003.

⁴ Using recommended adapter - not supplied.

⁵ USB operation can only be guaranteed on a PC with pre-installed Windows XP, Windows 2000, Windows Me, or Windows 98. USB 2.0 Hi-Speed performance requires Windows XP Service Pack 1, Windows 2000 Service Pack 4 or Mac OS X version 10.2.8 or later with pre-installed USB 2.0 port.

All specifications subject to change without notice. Print speeds may vary with computer system specifications and content of document printed. Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

