

you can
Canon

i-SENSYS
LBP5360



Fast, colour laser printer with PCL, networking and auto-duplexing as standard

The **i-SENSYS LBP5360** is part of the Canon laser printer range

The whole range consists of:
colour: **LBP5360**, LBP5300, LBP 5100, LBP5200 and LBP5000
mono: LBP3460, LBP3360, LBP3300, LBP3200, LBP3000 and LBP2900

Embargo Date: 23rd January 2007
Sales Start Date: Mid March 2007
Target Market: Small/Medium Enterprises – creative segment

Key Features

- Compact colour laser printer: 21 ppm in colour & mono
- Automatic double-sided printing as standard
- PCL5c/6 & UFR II* supported for maximum compatibility
- Quick First Print performance; zero warm-up time from sleep mode
- Fast 10 second first print time
- Network ready
- 128MB standard and 256 MB optional memory. Optional 20GB hard disk drive for heavy duty workloads
- 9600 x 600dpi - print resolution
- Colour All-in-One cartridges
- 250-sheet cassette, 1 00-sheet multi- purpose tray and optional 500-sheet cassette (max. A4)
- Windows, Mac** and Linux** compatible

* Canon's own printer language

** English only & web distribution only

Product Name	Mercury Code	EAN Code	Suggested Retail Price
i-SENSYS LBP5360	1314B014AA	8714574988054	£889

What's in the box: Main unit, Toner Cartridge 711BLK, 711 Yel, 711 Mag, 711 Cya, CD-ROM with Software and manual , set-up sheet, power cord, warranty card

Optional Accessories	Mercury Code	EAN Code	Suggested Retail Price
LB Printer Paper Cassette PF-93	1316B001AA	4960999403649	£339.29
LB Printer Exp.Ram ER-128	0646A039AA	4960999356990	£178.10
LB Printer Exp.Ram ER-256	0646A040AA	4960999356983	£249.63

New Consumables	Mercury Code	EAN Code	Suggested Retail Price
Cartridge 711 BLK	1660B002AA	4960999403809	£105.75
Cartridge 711 Yel	1657B002AA	4960999403717	£135.15
Cartridge 711 Mag	1658B002AA	4960999403748	£135.15
Cartridge 711 Cya	1659B002AA	4960999403779	£135.15

you can
Canon
i-SENSYS
LBP5360



Technical Specifications

ENGINE	
Printing speed	21ppm mono/colour (A4)
Printing method	LASER BEAM PRINTING
Fixing method	Colour On-Demand fixing
Resolution	600 x 600 dpi, 9600 x 600 dpi enhanced
Warm-up time	0 secs
First print	Approx 10.1 seconds (mono- and full-color)
Toner cartridge	Cartridges 711 CMYK (6000 pages at 5% coverage)
Toner Save	Yes
Paper Input (standard)	250-sheet cassette/100-sheets multi-purpose tray
Paper input.(Option)	500-sheets x1 (Maximum paper capacity 850 sheet)
Paper output	250 sheets (80 g/m ²)
Media size	Tray: A4, B5, A5, LGL, LTR, Executive, Foolscap, 16K Custom sizes: When loading paper in portrait orientation: Width 148.0 to 215.9 mm; Length 210.0 to 355.6 mm Multi-purpose: A4, B5, A5, LGL, LTR, Executive, Statement, Foolscap, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Envelope B5, Index Card Custom sizes: When loading paper in portrait orientation: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm
Media type	Tray: Plain paper (60 to 105 g/m ²) Multi-Purpose tray: Plain paper (60 to 105 g/m ²), heavy paper (106 to 220 g/m ²), Coated paper, Envelope, Label, Transparency
Duplex printing	Yes (built-in as standard/A4, Legal, Letter)
Power requirements	220-240V(±10%) 50/60Hz (±2Hz)
Power consumption	416W (Average during operation), Approx. 45W (Average during standby), Approx. 15W (Average during Power Save Mode 2)
Noise level	Max. 53 dB [A] or less (during operation) Max. 35 dB [A] or less (during standby)
Dimensions (W x D x H)	412mm x 470.7mm x 453mm
Weight (without cartridge)	Approx. 22 kg
Cartridge weight	1.2 kg each
Operating environment	Temperature: 10 to 30°C, Humidity: 10 to 80% RH (no condensation)
Energy Star Compliant	Yes

CONTROLLER HARDWARE	
RAM (Standard)	128 MB SDRAM (384 MB max.)
RAM (Optional)	128 MB SDRAM
ROM (Optional)	256 MB SDRAM
Interface (Standard)	USB 2.0 High Speed IEEE1284 (Parallel) 10Base-T/100Base-TX
Interface (Optional)	No
Hard disk (Optional)	YES- 20 Giga-byte (HD-93)
Other Features	Optional Paper Feeder PF-93
CONTROLLER SOFTWARE	
PDL (Standard)	PCL5c/ PCL 6/ UFR II
PDL (Optional)	No
Supported PC OS	* Operating System Software Microsoft Windows 98 Microsoft Windows Me Microsoft Windows 2000 Microsoft Windows XP Microsoft Windows Server 2003 Microsoft Windows VISTA Mac OS X 10.2.8 (English and web distribution) Linux (English and web distribution)
Supported Canon Application	* With Server-Based Computing Environment - Compatible Windows Terminal Server (Service) Microsoft Windows 2000 Server Microsoft Windows Server 2003 - Compatible Software Citrix MetaFrame XP Citrix MetaFrame 1.8 Citrix MetaFrame Presentation Server 3.0 Citrix Presentation Server 4.0
	NetSpot Device Installer/ NetSpot Console V4.10.2/ Remote User Interface
OTHER FEATURES	
Font (Standard)	80 Scalable fonts, 10 Bitmap fonts
Font (Optional)	None



Automatic Image Refinement

